WO 2006/043707 PCT/JP2005/019641

-23-

CLAIMS

1. A constant voltage power supply circuit
having an input terminal, an output terminal, a

5 constant voltage power supply unit that generates a
constant voltage with a ripple voltage, and a ripple
removing circuit unit for removing the ripple
voltage so that a constant voltage without the
ripple voltage is output at the output terminal,

10 the ripple removing circuit unit

comprising:

a resistor connected between the constant voltage power supply unit and the output terminal;

a ripple voltage detection circuit unit

15 for detecting the ripple voltage and outputting a signal depending on the detected ripple voltage; and

a current circuit unit for receiving a signal from the ripple voltage detection circuit unit and supplying a current to the output terminal or absorbing a current from the resistor in response to the received signal, so as to cancel the ripple voltage at the output terminal.

20

WO 2006/043707 PCT/JP2005/019641

-24-

2. The constant voltage power supply circuit as claimed in claim 1, wherein

the current circuit unit supplies a current when the received signal indicates that the ripple voltage is negative, and absorbs a current when the received signal indicates that the ripple voltage is positive.

- 3. The constant voltage power supply

 10 circuit as claimed in claim 1, wherein
 the current circuit unit comprises a
 current supplying circuit unit and a current
 absorbing circuit unit.
- 15
 4. The constant voltage power supply
 circuit as claimed in claim 3, wherein
 the current supplying circuit unit varies
 the supplied current depending on the received
 signal, and the current absorbing circuit unit
 20 varies the absorbed current depending on the
 received signal.

WO 2006/043707 PCT/JP2005/019641

-25-

5. The constant voltage power supplycircuit as claimed in claim 1, wherein

the product of a resistance value of the resistor and the supplied or absorbed current is equal to the ripple voltage.

6. The constant voltage power supplycircuit as claimed in claim 1, wherein

the ripple removing circuit unit further

10 comprises a capacitor connected between the output

terminal and an output of the current circuit unit.

- 7. The constant voltage power supplycircuit as claimed in claim 1, wherein
- the ripple voltage detection circuit unit receives the voltage from the constant voltage power supply unit, compares the received voltage with a reference voltage, and outputs the signal in accordance with the comparison.

20

25

5

8. The constant voltage power supply circuit as claimed in claim 1, wherein

the constant voltage power supply unit and the ripple removing circuit unit are integrated into one IC.